



QUALITY MANAGEMENT SYSTEM

UR.40-SD-U4021.0

REVISION NO

PAGE

5

1/1

PHTHALIC ANHYDRIDE PRODUCT SPECIFICATION

TRADE NAME : PHTHALIC ANHYDRIDE

GUARANTEED VALUES :

<u>TESTS</u>	<u>UNIT</u>	<u>VALUE</u>	<u>METHOD</u>
Phthalic anhydride	% w	Min. 99.8	PETKIM-G2-40D04
Oxidable matter (Maleic anhydride)	% w	Max. 0.05	PETKIM-G2-40D01
Solidification Point	°C	Min. 130.9	PETKIM-G2-40D05
Platinum Cobalt Color		Max. 20	ASTM-D-3366
Color Stabilization		Max. 50	ASTM-D-3366
Acidity (Free)	% w	Max. 0.5	PETKIM-G2-40D02

APPEARANCE : Flake

PACKING : In 25 kg FFS (Form Fill Seal) white colored PE bags
or 500,750,1000 kg big-bag

STORAGE CONDITIONS : Storage in dry closed and well ventilated areas is recommended

APPLICATION : In the production of plastifiers, paint and polyester.

MSDS NO : UR.40-BF-TE001-ING

GN - YS - FO - 00001